

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
 "Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

164.008 **Bulkhead Panels**

ASK CORPORATION 5-5, TSURUMICHUO 2-CHOME TSURUMI-KU, YOKOHAMA 230 JAPAN

| | | | |
|----------------|----------|---|---------------------------------|
| 164.008/0092/0 | APPROVED | "ASK Marilite G-P", 19 mm & 22 mm thick at 42-1/2 lb./cu. ft., may be used | only as a component of A-15 con |
| 164.008/0124/0 | APPROVED | "ASK Marilite SR-O", 50 mm thick, may be used as a component of A-30 constr | uction. |

BLOHM & VOSS AG POSTFACH 100720 HAMBURG 1 GERMANY

| | | | |
|----------------|----------|--|------------------------------|
| 164.008/0110/0 | APPROVED | "M1000-D" Bulkhead panels approved as meeting Class B-15 requirements, and | as a component in Class A- |
| 164.008/0111/0 | APPROVED | "M1000-S" Bulkhead panels. Approved as meeting Class B-15 requirements in | 50 mm (2 inch thickness), an |

BNZ MATERIALS, INC 6901 SOUTH PIERCE STREET SUITE 260 LITTLETON CO 80123

| | | | |
|----------------|----------|---|--------------------------------------|
| 164.008/0094/1 | APPROVED | "Marinite M" calcium silicate panel approved as meeting Class B-15 | requirements in 3/4 inch thickness a |
| 164.008/0103/0 | APPROVED | "Marinite ML" calcium silicate panel approved as meeting Class B-15 | requirements in 3/4 inch (19 mm) m |

BU-IL INDUSTRIES CO. LTD. 35 SOZOO-RI WOONGSANGMYUN YANGSAN-GUN KYUNGNAM S KOREA

| | | |
|----------------|----------|---|
| 164.008/0136/0 | APPROVED | BIP W-108 steel-faced mineral wool bulkhead panel. |
| 164.008/0144/0 | APPROVED | "BU-IL BIP W-102" steel-faced mineral wool bulkhead panels. |

CAPE INDUSTRIAL PRODUCTS, LTD GERMISTON WORKS PETERHILL RD SCOTLAND GLASGOW UNITED KINGDOM

| | | | |
|----------------|----------|---|-------------------------------|
| 164.008/0084/0 | APPROVED | "Cape Marine Board", calcium silicate panels approved as meeting Class B-15 | requirements in 19mm min. thi |
|----------------|----------|---|-------------------------------|

CLESTRA HAUSERMAN, INC. 29525 FOUNTAIN PARKWAY SOLON OH 44139

| | | | |
|----------------|----------|---|-----------------------------|
| 164.008/0064/1 | APPROVED | "Double Wall" steel-faced gypsum marine bulkhead panel system approved as | meeting Class B-15 requirem |
|----------------|----------|---|-----------------------------|

DANSK ETERNIT-FABRIK AS SONNGAARDSHOLMSVEY 2 PO BOX 763 AALBORG DENMARK

| | | |
|----------------|----------|---|
| 164.008/0119/0 | APPROVED | "Navalite N", 3/4" (19 mm) thick at 50 lb./cu. ft. (800 kg./cu. m). |
|----------------|----------|---|

HOPEMAN BROTHERS, INC 435 ESSEX AVE WAYNESBORO VA 22980

| | | | |
|----------------|----------|---|---------------------------------|
| 164.008/0066/0 | APPROVED | "Memphis 1-3/8" bulkhead panel , approved as meeting Class B-0, may not be | used as a component of A-CI |
| 164.008/0067/0 | APPROVED | "Memphis 2-1/32" bulkhead panel, approved as meeting Class B-0, may not be | used as a component of A-CI |
| 164.008/0068/0 | APPROVED | Hopeman Brothers' "Beta 100" steel-faced gypsum building unit, approved as | meeting Class B-15 requiremen |
| 164.008/0142/0 | APPROVED | Type "Verma-Light-T" Vermiculite panels approved as meeting Class B-15 | requirements in min. thickness |
| 164.008/0143/0 | APPROVED | Type "Verma-Light-F" Vermiculite panels approved as meeting Class B-15 | requirements in min. thickness |
| 164.008/0147/0 | APPROVED | "Sigma 100" double wall glass mat gypsum panels meeting Class B-15 criteria | in a minimum thickness of 1/2 i |

ISOLAMIN AB S-951 84 LULEA SWEDEN

| | | | |
|----------------|----------|---|--------------------------------|
| 164.008/0095/0 | APPROVED | Type 33A mineral wool core, steel-faced bulkhead panels, 50 mm thick. | |
| 164.008/0096/0 | APPROVED | Type 33C50 steel-faced mineral wool panels approved as meeting class B-15 | requirements in minimum thick |
| 164.008/0097/0 | APPROVED | Type 45A two mineral wool core, steel-faced bulkhead panels, separa ted by | 30 mm air gap, 80 mm thick. |
| 164.008/0106/1 | APPROVED | Type "33E50" steel-faced mineral wool panels approved as meeting Class B-15 | requirements in minimum thic |
| 164.008/0107/1 | APPROVED | "Ecomax Wall Element 671", 2" thick. | |
| 164.008/0127/0 | APPROVED | Type 42C50 and 42C70 steel-faced mineral wool panels, approved as meeting | Class B-15 requirements in m |
| 164.008/0128/0 | APPROVED | Type 43C50 and 43E50, 50 mm thick. | |
| 164.008/0138/0 | APPROVED | Type 30C50 steel-faced fiberglass wool bulkhead panels, approved as meeting | Class B-15 requirements in a |
| 164.008/0139/0 | APPROVED | Type 33C25 steel-faced mineral wool bulkhead panels, approved as meeting | Class B-O requirements in a mi |

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
 "Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

JAMESTOWN METAL MARINE SALES, INC 4710 NORTHWEST SECOND AVE SUITE 400 BOCA RATON FL 33431

| | | | |
|----------------|----------|--|--------------------------------|
| 164.008/0115/0 | APPROVED | "Unimet B-1" steel-faced gypsum bulkhead panels, appr. as meeting Class | B-15 req. with an omega joint. |
| 164.008/0116/0 | APPROVED | "Unimet B-1" steel-faced gypsum bulkhead panels, approved as meeting Class | B-0 req. with an H-Post joint. |

KELLER-KLINGNAU KLINGNAU 5313

| | | | |
|----------------|----------|---|--------------------------------|
| 164.008/0117/0 | APPROVED | "Vermipan", 19 mm thick at 810 kg/cu. m, may be used as a component of A- | 60 construction with omega joi |
|----------------|----------|---|--------------------------------|

KVAERNER MASA-YARDS INC. PIIKKIO WORKS SF-21500 PIIKKIO FINLAND

| | | |
|----------------|----------|--|
| 164.008/0131/0 | APPROVED | Type "WAS" steel-faced mineral wool bulkhead panels. |
|----------------|----------|--|

LIFETIME INDUSTRIES, INC 412 ASH MCALLEN TX 78501

| | | |
|----------------|----------|---|
| 164.008/0098/0 | APPROVED | Marine Environmental Systems, Inc. bulkhead panel. |
| 164.008/0099/0 | APPROVED | Marine Environmental Systems, Inc. bulkhead panel. |
| 164.008/0140/0 | APPROVED | Bulkhead panel assembly consisting of calcium silicate panels and mineral wool, approved as meeting class |

NORAC AS P. O. BOX 1593 MYRENE ARENDAL NORWAY

| | | |
|----------------|----------|--|
| 164.008/0034/0 | APPROVED | |
| 164.008/0134/0 | APPROVED | AKERPANEL Type C-600 steel-faced mineral wool bulkhead panels. |
| 164.008/0135/0 | APPROVED | AKERPANEL Type K-600 steel-faced mineral wool bulkhead panels. |

PABCO DIV. OF FIBREBOARD CORP 1110-16 ROAD FRUITA CO 81521

| | | |
|----------------|----------|---|
| 164.008/0109/0 | APPROVED | Pabco "Super Marine Temp" bulkhead panels. |
| 164.008/0125/0 | APPROVED | Pabco "Super Marinetemp", bulkhead panels approved as meeting class B-15 requirement in 3/4" inch thick |
| 164.008/0133/0 | APPROVED | PABCO "Super Marinetemp" bulkhead panels and structural insulation, approved as meeting A-60 bulkh |
| 164.008/0141/0 | APPROVED | PABCO "Marinetemp" bulkhead panel assembly consisting of calcium silicate panels and mineral wool, appr |

ROCKFON A/S HOVEDGADEN 501 HEDEHUSENE DENMARK

| | | |
|----------------|----------|---|
| 164.008/0104/0 | APPROVED | "TNF Type 3S", bulkhead panels approved as meeting Class B-15 requirements, in an overall thickness of 50 |
| 164.008/0118/0 | APPROVED | "TNF" TYPE 2 S" bulkhead panels, |
| 164.008/0126/0 | APPROVED | "TNF Type 2S", steel-faced mineral wool bulkhead panels, approved as meeting class B-15 requirements |
| 164.008/0137/0 | APPROVED | TNF Type 9S steel-faced mineral wool bulkhead panels. |

SBA INTERIOR OY SVARTA BRUK AB SVARTA FINLAND

| | | |
|----------------|----------|--|
| 164.008/0122/0 | APPROVED | JMC-Type 33 dB, approved as meeting Class B-15 requirements in 50mm minimum thickness and 150 kg/cu. |
|----------------|----------|--|

THERMAX BRANDSCHUTZBAUTEILE G.M.B.H. A-3300 GREINSFURTH

| | | |
|----------------|----------|--|
| 164.008/0114/1 | APPROVED | "Thermax SN" Vermiculite panels approved as meeting Class B-15 requirements in min. thickness of 19 mm a |
| 164.008/0146/0 | APPROVED | Type "Thermax SN Double Shell Partition" vermiculite panels approved as meeting Class B-15 criteria. |

TODCO DIV OF OVERHEAD DOOR CORP RTE 353 CATTARAUGUS NY 14719

| | | |
|----------------|----------|---|
| 164.008/0145/0 | APPROVED | TODCO Type "TD1" and "TD2" steel-faced mineral wool panels meeting Class B-15 req. in minimum thi |
|----------------|----------|---|

USG INTERIORS, INC. 700 N. HIGHWAY 45 LIBERTYVILLE IL 60048

| | | |
|----------------|----------|--|
| 164.008/0101/0 | APPROVED | "Crusader Marine" double wall gypsum bulkhead panels, approved as meeting Class B-15 requirements. |
|----------------|----------|--|

ASBERIT SA PO BOX 716 RIO DE JANEIRO BRAZIL

U. S. Coast Guard Equipment List

ALL EQUIPMENT LISTED BELOW IS USCG ACCEPTED AND MAY BE USED AS LONG AS IN GOOD AND SERVICEABLE CONDITION
"Approved" items are approved for manufacture - "Former May Use" items are no longer manufactured

164.008/0113/0 FORMER-MAY USE "Thermolite 650 SA", 7/8" (22 mm) thick at 50 lb./cu. ft. (800 kg/cu. m), may not be used as a component of A

NICHIAS CORP NO 1-26, 1-CHOME SHIBADAIMON, MINATU-KU TOKYO 105 JAPAN

164.008/0093/0 FORMER-MAY USE "Marine Board K-650" w/ "Omega" joint, density 40 lb./cu. ft., approved as Class B-0, may not be used in A-CI

164.008/0105/0 FORMER-MAY USE "Marine Board K-650" bulkhead panels, approved as meeting class B-15 requirements .